

DRIVEN BY AIR.



Dropout® Portable

Cost-effective portable water removal solution.

The Dropout® Portable Water Separator is a small portable unit enabling flexible installations for applications requiring a portable solution.

This cost-effective solution provides all the protection you need in one device instead of having to purchase and maintain a multiplicity of different products as it has the exact same water removal efficiency and characteristics of the smaller compact dropout units (>99.9999% efficiency) and has an integrated auto drain to ensure that liquid water and contamination is efficiently removed.

PRODUCT OVERVIEW

- 32 cfm flow rate
- 15 bar maximum pressure
- 1 micron particulate removal
- >99.9999% liquid water removal
- Built in auto drain

www.pclairtechnology.com



A HORNGROUP BRAND

Key Product Features & Benefits

- Portable - small and lightweight enough to carry to your point of use
- Plug and play - transfer easily between applications
- Pressure gauges as standard
- Integrated auto-drain (no power or batteries required)
- 99.9999% liquid water removal
- Particle removal 1 micron
- No replacement filter element

Part No. PDO900T8/R

Operating Specification

Flow rate:	32 cfm / 900 l/min
Maximum inlet pressure:	15 bar
Working pressure:	1-15 bar / 15-217 psi
Pressure drop:	0.38 bar / 5.51 psi
Operating temperature:	0 - 80 °C / 32 - 176 °F

Mechanical Specification

Inlet / Outlet:	3/4" BSPT
Water storage:	640 cc
Drain connection:	1/2" Automatic
Material:	Mild steel powder coated
Weight:	9.3 kg
Dimensions	520 x 320 x 235 mm

Approvals

Certified to:	ISO 12500 parts 3 & 4
---------------	-----------------------