

Model Specification Sheet

Part No. APT721

6" (150mm) Orbital Sander

This Orbital Sander is ideal for sanding and surface preparation on wood, metal, fibreglass and composite materials. It has a 150mm backing pad for use with Velcro abrasives with holes, allowing you to dust while sanding. The sander runs at a high speed of 12000 revolutions per minute (rpm), which allows it to smooth out very coarse surfaces with ease.

Features and Benefits

- Air inlet size of BSP 1/4"
- Pad size 152mm
- Speed 12,000 rpm
- Vibration level of 4.68 m/s²
- · Ergonomic design for comfort
- · Professional performance, built for durability

ica (rnm)	Carlot Carlot	
(rpm), rfaces	SHIN STATE OF A	
	6 SANULTO	
itv		

Air Inlet Thread Size Flow Rate 4.5cfm / 128 l/min Handle Type Ergonomic No Load Speed 12,000rpm Paper Fastening Type Velcro Weight 0.92kg Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	SPECIFICATIONS	
Handle Type Ergonomic No Load Speed 12,000rpm Paper Fastening Type Velcro Weight 0.92kg Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	Air Inlet Thread Size	¼" BSP
No Load Speed 12,000rpm Paper Fastening Type Velcro Weight 0.92kg Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	Flow Rate	4.5cfm / 128 l/min
Paper Fastening Type Weight O.92kg Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	Handle Type	Ergonomic
Weight 0.92kg Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	No Load Speed	12,000rpm
Orbits Per Minute 12,000 Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	Paper Fastening Type	Velcro
Sanding Disc Diameter 6" (150mm) Sound Pressure Level 86.8 dBa	Weight	0.92kg
Sound Pressure Level 86.8 dBa	Orbits Per Minute	12,000
	Sanding Disc Diameter	6" (150mm)
Vibration Loyal 4.69 m/s2	Sound Pressure Level	86.8 dBa
4.00 III/S ²	Vibration Level	4.68 m/s ²

